

Customized Basic PDU – I phase

Customized IT rack power distribution: Robust PDU with compact basic power distribution for the IT environment. Specification as customer’s request.



Features

Model No.	7979099
Product series	SWP8860 series
Product description	Compact basic power distribution. Thanks to the PDU basic, any IT rack can easily be equipped with a professional power distribution system. Depending on the PDU design, horizontal mounting in the 482.6 mm (19") level or vertical mounting is possible
Material	Solid black aluminum alloy shell Slots: Plastic
Supply includes	Assembly parts
Options	Top or bottom infeed Other frame colours are available
Dimensions	Depending on customer’s request
No. of sockets and type	IEC320 C13 & IEC320 C19 sockets with/without locking function, no. of sockets depending on customer’s request.
Rated operating voltage	250 V (AC), 50/60 Hz
Rated current (max.)	16A / 32A / 63A
Power consumption	4 kW / 8 kW / 15 kW
Infeed(s)	Qty.: 1 Phases per infeed: 1~
Length of connection cable	3 m
Type of electrical connection	CEE (250VAC 2P+E, IP44)

Customized Basic PDU – I phase

Compliance	CE, RoHS
Standards	EN 55032 EN 55035 EN IEC 61000-3-2 EN IEC 61000-3-3
Operating temperature range	0°C ... 45°C
Ambient humidity (non- condensing)	5% ... 95 %
Storage temperature range	-20°C ... 70°C
Packs of	1 pc(s)
Stock code	Yxxxxxx (x- 6 digits depending on PO)