

# Customized Basic PDU – 3 phase

Customized IT rack power distribution: Robust PDU with compact basic power distribution for the IT environment. Specification as customer’s request.



## Features

Model No.	7979099
Product series	SWP8860 series
Product description	Compact basic power distribution. Thanks to the PDU basic, any IT rack can easily be equipped with a professional power distribution system. Depending on the PDU design, horizontal mounting in the 482.6 mm (19") level or vertical mounting is possible
Material	Solid black aluminum alloy shell Slots: Plastic
Supply includes	Assembly parts
Options	Top or bottom infeed Other frame colours are available
Dimensions	Depending on customer’s request
No. of sockets and type	IEC320 C13 & IEC320 C19 sockets with/without locking function, no. of sockets depending on customer’s request.
Rated operating voltage	380-400 V (AC), 50/60 Hz
Rated current (max.)	16 A / 32 A
Power consumption	11 kW / 22 kW
Infeed(s)	Qty.: 1 Phases per infeed: 3~
Length of connection cable	3 m
Type of electrical connection	CEE (400VAC 3P+N+E, IP44)

# Customized Basic PDU – 3 phase

Compliance	CE, RoHS
Standards	EN 55032 EN 55035 EN IEC 61000-3-2 EN IEC 61000-3-3
Operating temperature range	0°C ... 45°C
Ambient humidity (non- condensing)	5% ... 95 %
Storage temperature range	-20°C ... 70°C
Packs of	1 pc(s)
Stock code	Yxxxxxx (x- 6 digits depending on PO)