

Customized Smart PDU - 3 phase

Customized IT rack power distribution: Smart PDU with energy measurement per phase, i.e. output requirement of an entire IT rack. Specification as customer’s request.



Features

| | |
|-----------------------------------|---|
| Model No. | 7979099 |
| Product series | SWP8860 series |
| Product description | Compact smart power distribution unit. Thanks to the PDU smart, any IT rack can easily be equipped with a professional power distribution system. Depending on the PDU design, horizontal mounting in the 482.6 mm (19") level or vertical mounting is possible |
| Material | Solid black aluminum alloy shell Slots: Plastic |
| Supply includes | Assembly parts |
| Options | Top or bottom infeed Other frame colours are available |
| Monitoring & LCD display | Voltage (V), Current (A), Power (kW) , Power consumption (kWh), Temperature and humidity |
| Metering Accuracy | +/- 1% |
| Communication | HTTP/HTTPS, SNMP v1/v2/v3, SNTP, RS485 and other communication protocols |
| Setting values for warning /alarm | Yes |
| PDU cascading | Up to 5 PDUs can be cascaded via the network interface |
| Dimensions | Depending on customer’s request |
| No. of sockets and type | IEC320 C13 & IEC320 C19 sockets with/without locking function, no. of sockets depending on customer’s request. |
| Rated operating voltage | 380-400 V (AC), 50/60 Hz |
| Rated current (max.) | 16 A / 32 A |
| Power consumption | 11 kW / 22 kW |

Customized Smart PDU - 3 phase

Infeed(s)

Qty.: 1

Phases per infeed: 3~

| | |
|------------------------------------|---------------------|
| Length of connection cable | 3 m |
| Type of electrical connection | CEE (400VAC 3P+N+E) |
| Compliance | CE, RoHS |
| Standards | EN 55032 |
| | EN 55035 |
| | EN IEC 61000-3-2 |
| | EN IEC 61000-3-3 |
| Operating temperature range | 0°C ... 45°C |
| Ambient humidity (non- condensing) | 5% ... 95 % |
| Storage temperature range | -20°C ... 70°C |
| Packs of | 1 pc(s) |